

Betonband

All-weather cloth tape (from -10 °C up to +60 °C); it can even be used on stones and irregular surfaces. Thanks to its great versatility, this product is suitable for all kinds of repairs, do-it-yourself applications and for the agricultural and building sectors.



ADVANTAGES AND PERFORMANCES

- Good adhesiveness on irregular surfaces
- High adhesiveness
- Accurate tear
- Removable without tearing

TECHNICAL PROPERTIES

		tolerance	test method
Backing:	PE laminated with polyester		
Adhesive:	Hot Melt		
Total weight:	155 g/m ²	± 10 %	ISO 536
Total thickness:	175 µm	± 10 %	AFERA 5006
Tensile strength:	min. 30 N/cm		AFERA 5004
Elongation at break:	min. 10 %		AFERA 5004
Adhesion to steel:	min. 6 N/cm		AFERA 5001
Temperature resistance:	up to 60 °C		
Rolling ball tack:	max 0,5 cm		PSTC 6
Colour:	yellow		

The above values are the result of arithmetic averages from tests on sample productions and are not legally binding.

ARTICLES, DIMENSIONS AND BARCODES

	dimensions	pieces per box	barcode
Betonband yellow:	48 mm x 50 m	24 rolls	8051499033989

OUR PROPOSAL OF PACKAGING

- Loose roll
- Sleeve with coloured half moon label

RECOMMENDATIONS

It's a good rule to use the product within 6 months from purchase, because the unwinding force of the tape increases with time. The product must be stored in its box in a dry location protected from sunlight, at about 15 °C - 25 °C and 50% relative humidity. If stored in different conditions, the product must be reconditioned. After application, the removal of the tape must be done slowly without tears. Before applying the tape, always check if the surface is clean. Euromask disclaims any liability for any direct or indirect damage coming from the misuse of the product. Under normal conditions, the tape is not toxic and is not approved for medical use.

The a.m. values may be changed at any moment for production needs or technical updates.

rev. 31_July 2019